

## AMERICA



## August 2023 Retail Price Guide

Model	Image	Description	Finish	Dimensions WHD Inches	Shipping Weight lbs	UP* USD
Class AB	Integrated Amplifiers					
L-505uXII		Updated Mark II Version Now Features ODNF 4.0 & Discrete Pre -amplifier Buffer Circuit. Class AB, 100W 8 $\Omega$ , 150W 4 $\Omega$ , Remote. §	Silver	17.3 x 7.0 x 17.9	60.3	5295
L-507Z		Improved Throughout, Features Newly Designed LIFES Feedback	Silver	17.3 x 7.0 x 17.9	65.0	8995
		Engine, Class AB, 110W 8 $\Omega$ , 210W 4 $\Omega$ , LIFES 1.0 Amplifying Circuit Output, LECUA 1000, 12V Trigger, IR Control, Remote. §			NEW	
L-509Z		Single Chassis Separate. Class AB, 120W 8 $\Omega$ , 240W 4 $\Omega$ , 2 x LIFES	Silver	17.3 x 7.6 x 18.2	84.0	12495
		Feedback Engine, 3-band Tone- EQ, LECUA EX, Peel coat ampli- fier and audio circuit boards, 12v Trigger, IR Control Remote. § !!		NEV	V Pre Ord	er
Control A	mplifiers					
C-10X	Lunghing	Fully Updated With LIFES & LECUA-EX, 3 x Single Ended	Silver	17.3 x 5.1 x 16.9	59.7	19995
		Inputs + 3 Balanced XLR, 2 Line Level Outputs + 2 Balanced XLR, Tape Loop, External Pre In, 12V trigger, Control In / Out, Remote Control. § !!			NEW	
C-900u		Control Pre-Amplifier. 3 x Single Ended Inputs + 3 Balanced XLR, 2 Line Level Outputs + 2 Balanced	Silver	17.3 x 5.1 x 16.9	59.4	15995
		XLR, Tape Loop, External Pre In, 2 x Remote out § !!		** bundle	w/ M-10X	only
Stereo Po	wer Amplifiers					
M-10X		Stereo Power Amplifier, Class AB Equipped With LIFES amplifica-	Silver	17.3 x 8.8 x 19.1	125.4	19995



Stereo Power Amplifier, Class AB Equipped With LIFES amplification feedback engine. 150W  $8\Omega$ Stereo, 300W  $4\Omega$  Stereo, 600W  $8\Omega$  Monaural. § !!

§ Core Luxman Product
!! Ultimate Fidelity Product

Model	Image	Description	Finish	Dimensions WHD Inches	Shipping Weight lbs	UP* USD
CD-Play	ers / SACD-Players					
D-N150		Completely Updated NeoClassico	Silver	11.7 x 3.9 x 8.7	17.6	2795
		CD Player, TI PCM 5102 DAC Chipset, 192Hz/32 Bit, Coax & Op- tical Input, USB Input 192/32, Opti- cal Output, Remote Included.		Subject T	o Availab	ility
D-03x		CD Player With MQA & USB DSD Support. Supports MQA-CD & MQA Files, 2x32 bit TI PCM1795, USB PCM 384kHz 32bit, USB DSD 11.20MHz 1bit, Remote §	Silver	17.3 x 5.2 x 16.1	29.6	4195
D-07x		SACD Player With MQA & USB DSD Support, LxDTM v2 Proprie-	Silver	17.3 x 5.2 x 16.1	44.0	9995
		tary Mechanism, ROHM BD34301EKV, USB PCM 746kHz 32bit, USB DSD 22.5MHz 1bit, MQA, 12V Trigger & Control In/ Out, Remote §		Ν	IEW	
D-10x	- O	SACD Player With MQA & USB DSD Support. LxDTM v2 Proprie- tary Mechanism, ROHM BD34301EKV, USB PCM 746kHz 32bit, USB DSD 22.5MHz 1bit, MQA, Fully Balanced, Remote § !!	Silver	17.3 x 6.1 x 16.5	69.0	16995
High Qu	ality Passive Signal Switchers					
AS-44	0000	Passive Line Level Switch, Line- Level Selector With RCA Inputs For Up To Four Sources. 6N OFC Wir- ing (99.99997% Pure Copper), Gold Plated Terminals	Gold	14.6 x 2.8 x 5.4	6.0	750

	 	ÓÓ	000		
				and the	7
1					1

AS-55



§ Core Luxman Product !! Ultimate Fidelity Product

Model	Image	Description	Finish	Dimensions WHD Inches	Shipping Weight lbs	UP* USD
Vacuum T	Tube Integrated Amplifier					
SQ-N150		Completely Updated NeoClassico Tube Integrated Amplifier, 4xJJ Electronic EL84, 2xJJ Electronic ECC83, 10W $6\Omega$ Push-Pull Design, Three Line Inputs, Phono Input with MM/MC Selection, Headphone In- put. Remote Controllable via D- N150 Remote OR RA-25	Silver	11.7 x 7.4 x 9.9	35.2	3495
LX-380		Integrated Amplifier Combining Vacuum Tube 6L6GC Based Output Section With 590AXII Pre-Amp Section. 20W $6\Omega$ , 18W $8\Omega$ , 14W $4\Omega$ , LECUA, In-Built Phono Stage, Definable Tone Controls, Remote. §		17.3 x 7.8 x 15.9	47.3	8495
Vacuum T	Tube / Solid State CD-Player					
D-380		CD Player With Selectable Transis- tor And Vacuum Tube Output Modes. TI PCM 5105 A DAC, 192 kHz 32 bit, ECC 82, Remote. §	Silver Front W/ Wood Case	17.3 x 6.6 x 11.3	30.8	5495
Vacuum T	Tube Control Amplifier					
CL-38uC		Vacuum Tube Control Pre- Amplifier With In-Built Phono Stage MM/MC, 1xBAL Input, 4xR- CA Input, Tone Controls And Re- mote. Uses High Voltage Metal- lized Polypropylene Film Capaci- torts, 3xECC83 and 5xECC82 Shunt Regulated Push Pull Config. §	W/ Wood Case	17.3 x 6.7 x 12.1	39.4	6395
CL-1000		Vacuum Tube Control Pre- Amplifier With In-Built Phono Stage MM/MC, LECUTA Trans- former Coupled Attenuator, 2xBAL & 2xRCA Output, 1xBAL & 4xR- CA Input, MM /MC Phono Input With Selectable Loading, 6xE88CC, Tone Controls § !!	Silver / Rosewood	18.1 x 6.6 x 17.8	56.9	23995
Vacuum T	Sube Power Amplifiers					
MQ-88uC		Class A Vacuum Tube Power Amplifier. 25W $6\Omega$ Stereo, 25W $4\Omega$ Stereo, 25W $8\Omega$ Stereo, 2xECC83 2xECC82 and 4xKT88, Fixed & Variable Inputs, Separate $4\Omega$ , $8\Omega$ , 16 $\Omega$ Taps. §	Silver / Brown	17.3 x 7.2 x 9.1	42.7	6395

§ Core Luxman Product !! Ultimate Fidelity Product

LUXMAN America, Inc.

Model	Image	Description	Finish	Dimensions WHD Inches	Shipping Weight lbs	UP* USD
Phono An	plifiers					
E-250		Solid State Compact Reference Pho- no Equalizer Amplifier. User Se- lectable Load Impedance (34/47/56/100 kΩ), User Selectable Load Capacitance (0/100/220/320 pF), Supports Low Impedance MC Cartridges	Silver	14.3 x 3.2 x 10.8	14.5	2395
Turntable	28					
PD-151 MF		Belt Drive Analog Turntable. 33/45/78 RPM With Independent Speed Control, Custom Luxman Tonearm With Universal Head Shell. §	Silver / Black Plinth	18.3 x 6.5 x 14.9	42.0	5695
		Optional 4mm Acrylic Hinged Dust Cover.	NA	18.2 x 4.4 x 14.7	11.0	795
PD-191A		Belt Drive Analog Turntable. 33/45/78 RPM With Independent	Silver / Rosewood	19.3 x 6.5 x 15.7	70.0	12495
		Speed Control & Stroboscope, Orig- inal SAEC LTA-710 10 Inch Arm With Universal Head Shell. §	Plinth	N	EW	
		Optional 4mm Acrylic Hinged Dust Cover.	NA	19.2 x 4.4 x 15.6	14.0	895

## rtriuge

	LMC-5
1	
1 20	

M ' 0 '1 + '1	D D 1170 100	1	2605
Moving Coil cartridge.	Deep Red 17.0mm x 18.3mm x	1	2695
SHIBATA needle, directly wound	21.3mm		
cross mounded coils with L/R sym-			
metrically wound power generation	M2.6mm x 2 mount-		
coils. Low-distortion structure using	g ing holes		
single point piano wire structure.			
Alumite body design.			

§ Core Luxman Product
!! Ultimate Fidelity Product

Model	Image Description	Finish	Dimensions WHD Inches	Shipping Weight lbs	UP* USD
<b>Optional Arn</b>	n Board (compatible with PD-191A, PD-171A, PD-171AL				
OPPD-AB1	Arm Board, SME3009R / 3010R and other 9" Tonearms	Silver			595
OPPD-AB2	Arm Board, FR64/64S/64FX IKEDA IT-345	Silver			595
OPPD-AB3	Arm Board, SAEC We-30B	Silver			595
OPPD-AB4	Arm Board, SAEC WE-407/23	Silver			595
OPPD-AB5	Arm Board, ORTOFON AS-212S/RS212D	Silver			595
OPPD-AB6	Arm Board, DIY Universal Tonearm Board	Silver			595
<b>Optional Seco</b>	ond Arm Board (compatible with PD-191A)				
OPPD-AB11L	Long Arm Base for Luxman PD-191A, For SME 3012 (12 inches)	Silver			995
Turntable Op	otions And Spare Parts				
PD-171BLT	Spare Belt for Luxman PD-171A / PD-151 / PD-191A	N/A			115
PD-171MAT	Spare Rubber Mat for Luxman PD-171A / PD-151 / PD-191A	Black			345
PD-191HS3	Spare Aluminium Headshell with D.U.C.C. conductors for PD-191A	Silver			295
PD-171HS1	Spare Magnesium Headshell for Luxman PD-171A	Silver			225
PD-151HS2	Spare Aluminium Headshell for Luxman PD-151A MKII	Silver			225
PD-191HW3	Heavier Counter Weight for Luxman PD-191A, 10-19g Cartridge or 23-32g Headshell & Cartridge	Silver			295
PD-171HW1	Heavier Counter Weight for Luxman PD-171 / PD-151, 9-19g Cartridge or 22-33g Headshell & Cartridge	Silver			225
PD-151HW2	Heavier Counter Weight for Luxman PD-151A MKII, 9-19g Cartridge or 22-33g Headshell & Cartridge	Silver			225

Model	Description		Finish	Dimensions WHD Inches	Shipping Weight lbs	UP* USD
Luxman P	remium Cables					
JPR-100	1.0m Standard RCA Cable, High-Purity Oxyge	en-free Copper	Black			320
JPR-150	1.5m Standard RCA Cable, High-Purity Oxyge	en-free Copper	Black			350
JPC-100	1.0m XLR Cable, High-Purity Oxygen-free Copper		Black			320
JPC-150	1.5m XLR Cable, High-Purity Oxygen-free Copper		Black			390
JPU-150C	1.5m USB Cable, High-Purity O-free Copper,	TYPE C—TYPE B	Black			270
JPU-150	1.5m USB Cable, High-Purity O-free Copper,	TYPE A—TYPE B	Black			270
Luxman R	eference 15000 Series Cables					
JPR-15000	Highly Pure New RCA Co adjustable Br	RCA Cable, 1.3m 7N DUCC* Copper, onnectors, User- anch Length, Non- bon Pigment.	Vivid Blue			1295
JPC-15000	Highly Pure Genuine Neu User-adjustal	XLR Cable, 1.3m 7N DUCC* Copper, tric XLR Connectors, ble Branch Length, Non rbon Pigment.	Vivid Blue			1295
JPS-15000	Highly Pure Newly Devel ors, User-adj Non-twisted	Speaker Cable, 3.0m 7N DUCC* Copper, oped Y-lug Connect- ustable Branch Length, Core Structure, Non- bon Pigment. (1 Pair)	Vivid Blue			3795

\*DUCC (Dia Ultra Crystallized Copper) is a registered trademark of Mitsubishi Cable Ind., Ltd.

§ Core Luxman Product
!! Ultimate Fidelity Product



## LUXMAN PRODUCTS ARE AVAILABLE THROUGHOUT THE UNITED STATES FROM A NETWORK OF TRAINED SPECIALTY AUDIO DEALERS.

FOR HELP LOCATING YOUR NEAREST AUTHORIZED LUXMAN DEALER EMAIL LUXMAN AMERICA AT SALES@LUXMANAMERICA.COM

> ADDITIONAL PRODUCT INFORMATION AVAILABLE AT HTTP://WWW.LUXMANAMERICA.COM

EMAIL LUXMAN AMERICA AT INFO@LUXMANAMERICA.COM

\*UP: Universal Price: Luxman America has issued a formal Universal Price Policy (UP Policy) as a formal written statement of its Policy that Luxman America authorized dealers are expected to abide by in advertising Luxman brand products to retail customers via any and all forms of published advertising, media and internet based advertising. The fundamental purpose of this Policy is to protect the Luxman brand in the marketplace, prevent dilution of the Luxman brand, uniformly protect Luxman America authorized dealers, promote a level playing field amongst dealers and to promote positive non-price driven competition among dealers. Full written policy available upon request.