



HARMAN LUXURY AUDIO

CONFIDENTIAL U.S. RETAIL PRICE LIST

Table of Contents

Preamplifiers	3
Players	4
Integrated Amplifiers	5
Power Amplifiers	6
Terms and Conditions	7

PREAMPLIFIERS



No523



No526



No5206

Model Name	Description	Material Number	MSRP
No523	<p>Dual-monaural Preamplifier with Pure Phono</p> <ul style="list-style-type: none"> • Analog Inputs: 2 balanced (XLR), 3 single-ended (RCA) line, 1 single-ended (RCA) phono w/ ground • Analog Outputs: 1 balanced (XLR); 1 pair single-ended (RCA), 1 headphone (1/4", 6.3mm TS) • Output Impedance: <80Ω single ended, <160Ω balanced • Dimensions (H x W x D): Height (with feet): 3.75" / Height (without feet): 3.25" x 17.25" x 18" (10.2cm/8.9cm x 43.8cm x 45.7cm) • Weight: 39 lbs (17.7kg) • Packaged dimensions (H x W x D): 26.7" x 16" x 26.7" (679 x 406 x 679mm) • Packaged weight: 64 lb (28.8 kg) 	<p>NO523 (120 Volt) UPC: 050667370756</p>	\$15,000.00/ea
No526	<p>Dual-Monaural Pure Path Preamplifier with Precision Link DAC and Pure Phono</p> <ul style="list-style-type: none"> • Analog Inputs: 2 balanced (XLR), 3 single-ended (RCA) line, 1 single-ended (RCA) phono w/ ground • Digital Inputs: 1 balanced (XLR); 2 coaxial (RCA); 2 optical (Toslink); 1 USB-B asynchronous • Analog Outputs: 1 balanced (XLR); 1 pair single-ended (RCA), 1 headphone (1/4", 6.3mm TS) • Output Impedance: <80Ω single ended, <160Ω balanced • Dimensions (H x W x D): Height (with feet): 3.75" / Height (without feet): 3.25" x 17.25" x 18" (10.2cm / 8.9cm x 43.8 cm x 45.7 cm) • Weight: 41 lbs (17.7kg) • Packaged dimensions (H x W x D): 26.5" x 16.3" x 26.5" (673 x 413 x 673mm) • Packaged weight: 63 lb (28.6 kg) 	<p>NO526 (120 Volt) UPC: 050667370794</p>	\$ 20,000.00/ea
No5206	<p>Preamplifier with PurePath fully discrete, direct-coupled, dual-monaural line-level class A preamp circuitry</p> <p>Analog input connectors:</p> <ul style="list-style-type: none"> • 2 pairs balanced line-level inputs (XLR) • 2 pairs single-ended line-level inputs (RCA) • 1 pair single-ended moving-coil phono inputs (RCA) • 1 pair single-ended moving-magnet phono inputs (RCA) <p>Digital audio connectors:</p> <ul style="list-style-type: none"> • 2 coaxial S/PDIF inputs (RCA) • 2 optical S/PDIF inputs (Toslink) • 1 balanced AES/EBU input (XLR) • 1 asynchronous USB input (USB-B) <p>Output connectors:</p> <ul style="list-style-type: none"> • 1 pair single-ended line-level outputs (RCA) • 1 pair balanced line-level outputs (XLR) <p>Control connectors:</p> <ul style="list-style-type: none"> • 1 RS-232 port (DB-9) • 1 Ethernet port (RJ-45) • 1 USB port for firmware updates (USB-A) • 1 baseband IR input (Ø"/3.5mm phone jack) • 1 programmable 12V DC trigger output, • 100mA maximum (Ø"/3.5mm phone jack) • 1 programmable 12V DC trigger input (Ø"/3.5mm phone jack) <p>Power consumption:</p> <ul style="list-style-type: none"> • Power on: 70W • Power on, headphones connected: 85W • Normal standby: 65W • Power Save standby: 4W • Green standby: <0.4W • Dimensions (H x W x D): 4.96 x 17.25 x 19.25" (126 x 438 x 489mm) • Packed Dimensions (H x W x D): 13.63 x 24.25 x 29" (346 x 616 x 737mm) • Net Weight: 34 lbs (15.4kg) • Packed Weight: 48 lbs (21.7kg) 	<p>MLNO5206AM UPC: 050667376505</p>	\$9,000.00/ea

PLAYERS



No519

- Audio Player
Now featuring ROON and MQA
- Slot loading CD player
 - Digital inputs: 1 balanced; 2 coaxial; 2 optical; 1 USB asynchronous, Bluetooth receiver
 - Mass storage: 2 USB type A
 - Network: Ethernet, Wi-Fi 802.11b/g/n
 - PCM input sample rates; 32, 44.1, 48, 88.2, 96, 176.4, and 192kHz
 - PCM input bit depth: up to 32
 - DSD: native, single (2.8MHz) and double-speed (5.6MHz)
 - Main analog outputs: 1 pair balanced; 1 pair single-ended
 - Headphone output: 1 1/4-inch (6.3mm)
 - Digital outputs: 1 balanced; 1 coaxial; 1 optical
 - Control I/O: Ethernet, RS-232, Trigger In and Out, IR In
 - Software update: Network, USB
 - Power requirements: 100, 115, or 230V AC, factory set for destination country
 - Control apps: iOS, Android, web browser
 - Dimensions: 17.25" x 16" x 5.75"
 - Weight: 36 lbs (16.4kg)
 - Packaged dimensions (H x W x D): 26" x 26" x 17" (660 x 660 x 432mm)
 - Packaged weight: 56 lb (25.5 kg)

NO519
(120 Volt)
UPC: 050667370718

\$20,000.00/ea



No5101

- Network Streaming CD/SACD Player and DAC
- 3-in-1 companion source for N°5805 or N°5802
 1. Slot Loading SACD Player
 2. Network Streamer
 3. DAC
 - Plays all disc formats, including CD/SACD, CD-A, CD-R and CD-RW
 - Supports FLAC, WAV, AIFF, OGG, MP3, AAC and WMA
 - USB -A for USB Drive file playback
 - PrecisionLink II DAC
- Technical Specifications:
- Output voltage: 3.0V RMS single-ended at full scale (0dBFS)
 - 6.0V RMS balanced at full scale (0dBFS)
 - Total harmonic distortion + noise:
 - <0.004%, 20Hz to 20kHz, single-ended, 3V RMS output (44.1kHz/16 bit signal)
 - <0.003%, 20Hz to 20kHz, balanced, 6V RMS output (44.1kHz/16 bit signal)
 - <0.003%, 20Hz to 20kHz, single-ended, 3V RMS output (192kHz/24 bit signal)
 - <0.002%, 20Hz to 20kHz, balanced, 6V RMS output (192kHz/24 bit signal)
 - Signal-to-noise ratio: >94dB single-ended (wideband, unweighted, referred to 3V RMS output)
 - >106dB balanced (wideband, unweighted, referred to 6V RMS output)
 - Power consumption: Standby: <0.4W
 - Power on: 32W

MLNO5101AM
UPC: 050667375829

\$5,500/ea



No5105

- Turntable
- Custom 10-inch tonearm
 - Precision roller ball bearings in all directions
 - Ultra-precision movement and damping
 - Digitally controlled 12V synchronous motor
 - Fully digital motor electronics with 33/45 speed selections
 - Stable speed and low wow/flutter
 - Global power supply
 - Massive solid brushed aluminum plinth precision machined from a single billet
 - 14lb solid aluminum platter - backside coated with resonance absorbing material
 - Adjustable isolated feet
 - Glass and aluminum front panel with speed and standby control
 - Integrated bubble level

MLNO5105AM
MLNO5105AMMC

\$6,000.00/ea

\$7,000.00/ea

INTEGRATED AMPLIFIERS



Model Name	Description	Material Number	MSRP
No585.5	<p>Integrated Amplifier with Phono Stage</p> <ul style="list-style-type: none"> • 200Wpc into 8 ohms 350Wpc into 4 ohms • Analog audio inputs: One XLR and three RCA stereo pairs • Phono inputs: One RCA stereo pair (configurable for MC/MM) plus ground terminal • Digital audio inputs: One USB, one AES/EBU, two coaxial and two optical • Analog audio outputs: One RCA stereo pair with selectable 80Hz crossover • Communication and control: Ethernet, USB, RS-232, IR input, and 12V trigger input and output • Remote control: IR system remote • Dimensions: 7.6" x 17.1" x 19.9" (193mm x 434mm x 506mm) • Weight: 74 lb (34kg) • Packaged dimensions (H x W x D): 26.4" x 18.9" x 26.4" (670 x 480 x 670mm) • Packaged weight: 96 lb (43.7 kg) 	<p>MLNO585P5AM UPC: 050667372378</p>	\$16,000.00/ea
No5805	<p>Integrated Amplifier with Phono Stage</p> <ul style="list-style-type: none"> • 125Wpc into 8 ohms 250Wpc into 4 ohms • Analog audio inputs: One XLR and two RCA stereo pairs • Phono inputs: One RCA stereo pair MC and one RCA stereo pair MM plus ground terminal • Digital audio inputs: One USB, one coaxial, two optical, Bluetooth aptX • MQA full decoding on all digital inputs including asynchronous USB • Analog audio outputs: One RCA stereo pair (variable) • Headphone output: One ¼-inch jack (front panel) • Communication and control: Ethernet, USB, RS-232, IR input, and 12V trigger input and output • Dimensions (H x W x D): 5.72" x 17.25" x 19.98" (145 x 438 x 507mm) • Packaged dimensions (H x W x D): 13" x 24" x 28" (330 x 610 x 711mm) • Packaged weight: 73 lbs (33kg) 	<p>MLNO5805AM UPC: 050667373481</p>	\$ 8,500.00/ea
No5802	<p>Integrated Amplifier</p> <ul style="list-style-type: none"> • 125Wpc into 8 ohms 250Wpc into 4 ohms • Analog audio inputs: None • Digital audio inputs: One USB, one AES/EBU, two coaxial, two optical, Bluetooth aptX • MQA full decoding on all digital inputs including asynchronous USB • Analog audio outputs: One RCA stereo pair (variable) • Headphone output: One ¼-inch jack (front panel) • Communication and control: Ethernet, USB, RS-232, IR input, and 12V trigger input and output • Dimensions (H x W x D): 5.72" x 17.25" x 19.98" (145 x 438 x 507mm) • Packaged dimensions (H x W x D): 13" x 24" x 28" (330 x 610 x 711mm) • Packaged weight: 72 lbs. (32.6kg) 	<p>MLNO5802AM UPC: 050667373542</p>	\$ 7,000.00/ea

POWER AMPLIFIERS



Model Name	Description	Material Number	MSRP
No536	<p>Monaural Amplifier</p> <ul style="list-style-type: none"> • Input connectors: one XLR Balanced, one RCA Unbalanced • Speaker connectors: two pairs of Hurricane loudspeaker outputs with banana-plug sockets (except on 230 VAC version) • Control connectors: Ethernet, RS-232, Trigger In, Trigger Out, USB-A, Mini USB • Rated output power: 400W RMS @ 8 ohms, 800W RMS @ 4 ohms, 20Hz to 20kHz at <0.3% THD, full output from 2.83VRMS • Frequency reponse: 10Hz to 20kHz +/- 0.2dB • Signal-to-noise ratio: >85dB, reference level 2.83 VRMS • Input impedance: 60 kΩ balanced; 30 kΩ unbalanced • Voltage gain: 26dB • Input sensitivity: 2.83 VRMS output at 142mVRMS input • Power requirements: 100V~, 120V~, 230V~; factory set for destination country, 1500W • Dimensions (H x W x D): 7.65" x 17.75" x 19.83" (119.4 cm x 45.1 cm x 50.4 cm) • Weight: 100 lbs (45.4kg) • Packaged dimensions (H x W x D): 26.6" x 15.4" x 28.3" (675 x 390 x 720mm) • Packaged weight: 119 lb (54.1 kg) 	<p>NO536 (120 Volt) UPC: 050667370831</p>	\$ 15,000.00/ea
No534	<p>Dual-Monaural Amplifier</p> <ul style="list-style-type: none"> • Input connectors: one pair Balanced, one pair single-ended • Speaker Connectors: four pairs of Hurricane loudspeaker outputs, banana-plug sockets per channel, except on European versions • Control I/O: Ethernet, RS-232, Trigger In and Out, USB-A, MiniUSB • Rated Output Power: 250 wpc RMS @ 8Ω, 20Hz to 20kHz @ <0.3% THD, full output from 2.83VRMS • Frequency Response: 10Hz to 20kHz ±0.2dB • Signal-to-Noise Ratio: >85dB, reference level: 2.83 VRMS • Input Impedance: 60 kΩ balanced; 30 kΩ unbalanced • Voltage Gain: 26dB • Input Sensitivity: 2.83VRMS output at 142mVRMS input • Power Requirements: 100V~, 120V~, 230V~, factory set for destination country, 1500W • Dimensions (H x W x D): (with feet): 7.75" (19.7cm) / (without feet): 7" x 17.75" x 20" (19.7cm/17.8cm x 45.1cm x 50.8cm) • Weight: 107 lbs (48.5kg) • Packaged dimensions (H x W x D): 0.7" x 17.8" x 7.8" (17.8 x 451 x 197mm) • Packaged weight: 124 lb (56.3 kg) 	<p>NO534 (120 Volt) UPC: 050667370671</p>	\$ 20,000.00/ea
No5302	<p>"Fully discrete, direct-coupled, dual monaural class AB amplifier</p> <ul style="list-style-type: none"> -Input connectors: 1 pair balanced line-level inputs (XLR) -1 pair single-ended line-level inputs (RCA) -Output connectors: 2 pairs high current multi-way binding posts on all units. -Control connectors: 1 RS-232 port (DB-9) -1 Ethernet port (RJ-45) -1 USB port for firmware updates (USB-A) -1 baseband IR input (Ø"/3.5mm phone jack) -1 programmable 12V DC trigger output, 100mA maximum (Ø"/3.5mm phone jack) -1 programmable 12V DC trigger input (Ø"/3.5mm phone jack) -Power consumption: Maximum: 1000W -On, idle (stereo mode): 90W -On, idle (bridged mode): 70W -Normal standby: 35W -Power Save standby: 2W -Green standby: <0.4W -Dimensions (H x W x D): 5.72 x 17.25 x 20.75": (145 x 438 x 527mm) -Packed Dimensions (H x W x D): 13.63 x 24.25 x 29" (346 x 616 x 737mm) -Net Weight: 70 lbs (31.7kg) -Packed Weight: 85 lbs (38.5kg) 	<p>MLNO5302AM UPC: 050667376543</p>	\$9,000.00/ea

Custom rack mounts available from Middle Atlantic: <http://www.middleatlantic.com/products/racks-enclosures.aspx>

Terms and Conditions of Sale

Terms of Payment – 4% 30, net 31 days (for qualified open accounts), unless otherwise agreed to by HARMAN Luxury Audio Group (LUX-A). The discounted price is for invoices paid within the stated terms. Prepaid and C.O.D. orders will receive the discounted price. Discount payment schedule is determined from the date of invoice to the date of full payment received. A FINANCE CHARGE, which is computed using a “periodic rate” of 1.5% per month (or an ANNUAL PERCENTAGE RATE of 18%), may be applied on all past-due accounts. Prices are subject to change without prior notice.

Acceptance of Orders – All orders are subject to the acceptance of LUX-A.

Shipments – All shipments will be made F.O.B. Lexington, KY, unless otherwise specified and at the discretion of LUX-A. Free shipping within the USA for all orders over \$2,500 (with exception to all “architectural product only” orders, free shipping will apply regardless of order size), of assorted LUX-A products per location, for shipment by surface carrier to one location at one time, using standard ground, within the 48 contiguous states. Express shipping is available at additional cost. Claims against LUX-A for shortages (where carrier is not at fault) must be made within ten (10) days after arrival of shipment.

Receipt of Shipment – Upon delivery of merchandise by LUX-A, to carrier, the merchandise becomes the property of the consignee. Claims for shortage or damages must be submitted to carrier within ten (10) days after receipt of shipment. It is the dealer’s responsibility to inspect the merchandise upon receipt for any possible external damage. If the merchandise is received in damaged condition, the delivering carrier should be notified in writing (Bill of Lading (BOL) should be signed “damaged” or “refused”) at the delivery point.

Returns – Effective March 1, 2009, all defective products will be authorized to be returned for credit only, unless otherwise stated. All product returns require advance authorization. Units returned without an authorization number will be refused. Credits for returned merchandise will be issued based upon Dealer purchased cost. All credits issued for returned merchandise found not to be defective will be assessed a 15% restocking charge, which will be deducted from credit issued. All credits for returns of incomplete systems will be based on the value of the component(s) that is/are returned. Merchandise authorized for return must be shipped prepaid freight. All authorized returns should be shipped in the original factory carton. Merchandise being returned must have the following information listed on the carton: Return Authorization (RA) #, Model #, Serial # and the number of units packed within the carton.

Stock Adjustments – All authorized returns for stock adjustments shall be subject to a restocking charge of 20%. Returns require a Return Authorization (RA) # issued by LUX-A and must be shipped freight prepaid.

ALL PRICES, SPECIFICATIONS, APPEARANCE, and TERMS AND CONDITIONS OF SALE ARE SUBJECT TO CHANGE WITHOUT NOTICE.

PRICES EFFECTIVE July 1, 2021



HARMAN Luxury Audio Group
8500 Balboa Blvd., Northridge, CA 91329 USA
Phone: 888-691-4171
Orders: luxurysales@harman.com
Technical Support: csupport@harman.com
www.MarkLevinson.com • www.facebook.com/MarkLevinsonAudio

© 2021 HARMAN International Industries, Incorporated. All rights reserved.

Mark Levinson and the Mark Levinson logo are trademarks of HARMAN International Industries, Incorporated, registered in the United States and/ or other countries. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. SACD is a trademark of Sony Corporation. VXP is a registered trademark of Sigma Designs, Inc., in the United States and/or other countries. All rights reserved.